

Superfinish Alkyd Interior Semi-Gloss Enamel M1700

Description:	Muralo's Superfinish Alkyd Semi-Gloss Enamel is a highly durable decorative interior finish characterized by its excellent hiding, toughness, adhesion, scrubability, spot and stain resistance. It can be washed repeatedly with soap and water without damage to the paint film. This low lustre finish is ideal for walls and woodwork, kitchens, baths, or any interior surface where maximum durability is required.
Recommended Uses:	For interior use on all previously painted surfaces, new and old metal surfaces, woodwork, and dry wall construction. Highly recommended for heavy use areas such as kitchens, baths, cabinets, doors, trim and children's rooms that may be contaminated with traces of body oils, waxes or cooking greases. Use it on any surface where a hard, scrubable finish is desired.
Surface Preparation:	<p>All surfaces must be clean and free from dirt, dust, grease, oil or peeling paint. Repair cracks and other imperfections with Spackle® brand surfacing compound. For large holes in plaster, use Muralo Patching Plaster.</p> <p><u>New or Unpainted Surfaces:</u> Priming is not required, but for best results over porous surfaces use Muralo Alkyd Primer Sealer #567 or Latex Enamel Undercoater #563</p> <p><u>Previously Painted Surfaces:</u> Previously painted surfaces in sound condition do not require a primer. Dull glossy areas by light sanding to ensure good adhesion.</p> <p><u>Metal Surfaces:</u> priming is not required for non-rusting metals such as aluminum or copper. Metals subject to rusting should be primed with Muralo Anti-Rust Primer. All metal surfaces should be free from peeling paint, oil, loose rust and scale before painting.</p>
Application:	<p>For best results, use:</p> <p><u>Brush:</u> A good quality synthetic or nylon bristle brush.</p> <p><u>Roller:</u> ¼" nap roller cover for smooth surfaces and 3/8" to ½" nap roller for rough and textured surfaces.</p> <p><u>Spray:</u> For airless a tip size from 0.018" to 0.021" is suggested with equipment that will maintain a sufficient fluid pressure to obtain an 8" to 10" fan at one foot distance. For conventional spray, use 0.028" to 0.07" fluid nozzle with air pressure to give 6" to 12" spray pattern at 8" to 12" distance.</p>
Finish:	Low Lustre Satin Finish. 60°Gloss = 40-50
Colors:	Available in White and a full line of tint bases for custom colors
Viscosity:	80-90 KU
Weight Per Gallon:	11.8 lbs. Per gallon

Revised 2/2/2004

Coverage:	Covers most surfaces in one coat. Contrasting colors and rough surfaces may require more than one coat.	
Spreading Rate:	400-450 sq. ft. per gallon. Less on porous and textured surfaces	
Dry Time:	Dries in 6 – 8 hours under normal conditions. May take longer to dry under humid conditions. Can be recoated after 24 hours.	
Thinning:	Not recommended. If necessary, up to ½ pint of mineral spirits per gallon of paint may be added.	
Flash Point:	101°F Closed Cup	
Federal Spec. Equivalent:	TT-E-508 or TT-E-509	
V.O.C. (V.O.S.)	Meets all V.O.C. and environmental regulations.	
Formulation:	Pigment* Titanium Dioxide, Types II, IV Calcium Carbonate Silica & Silicates Vehicle* Acrylic Terpolymer Resin Mineral Spirits Driers & Additives *Varies with individual products in the line.	
Packaging:	Per Case	Approx. Wgt.
	Gallons 4	51 lbs.
	Quarts 6	20 lbs.
Cautions:	Combustible!! Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing. Do not apply when temperature is below 40°F.	

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.