

Ceiling Paint M0268

Description:

- Designed to give a flat white non-glare finish with maximum reflection.
- Minimized lap marks and ceiling defects
- Easy latex application
- Covers in a single coat
- Quick 30-minute drying
- Pleasant fragrance
- Water clean-up

Recommended Uses:

Interiors only. Painted or unpainted plaster, wallboard, ceiling tile, primed wood, primed meal and tightly adhering wallpaper.

Surface Preparation:

To obtain good adhesion and best results the surface must be clean, free of dirt, dust, grease, oil, peeling paint and loose plaster. Watch for areas where there's been a buildup of grease, oil or soap film. This happens most often in kitchens and bathrooms. Wash those surfaces with water and detergent. Rinse thoroughly.

Patch cracks and other imperfections with Spackle[®]. Sand seal patched area with this latex paint. For large holes in plaster use Muralo Patching Plaster.

Water stains sometimes found on ceilings should be shellacked to prevent bleeding through.

To assure adhesion on glossy or slick areas, sand lightly or use a prime coat of Muralo Enamel Undercoat.

Unpainted Surfaces: New plaster should age at least 20 days and be primed with Muralo PVA Primer. Allow 2 hours for primer to dry. Drywall may require two coats.

How to apply:

This paint is ready to use right from the can. Just stir it thoroughly. Thinning is not recommended. Never add turpentine, oil or other paint thinners to latex paint. Temperature must be above 45°F for painting.

Application:

Apply generously with a 1/2 " Elder & Jenks Dual Coater roller or an Elder & Jenks synthetic bristle brush.

Keep roller or brush full (redipping for about every 2' X 2' area). Avoid excessive brushing or rolling. With spray equipment, use a nozzle that introduces air and paint separately.

Revised 3/5/2005

Best method for painting ceilings:

First, use a brush or edging tool to paint areas where ceiling meets the walls. "Cut in" to ceiling 4 or 5 inches. Then, attach a 4 ft. extension pole to roller and paint from a standing position on floor. This gives a better view and more control.

Environmental Information:

Free of Lead, Mercury and Pollution Hazards

HMIS

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Major Ingredients:

Ingredient	Cas#
Vinyl Acetate/Acrylic Copolymer	25067021
Titanium Dioxide	13463677
Aluminum Silicate	12068533
Silicone Dioxide	7631868
Ethylene Glycol	107211
Water	7732185

V.O.C.

Contains max 100 gms/ltr or 0.83 lbs/gal V.O.C.

Cautions:

Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Keep from freezing.

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.