

**Muralo 567 Alkyd Enamel Undercoater and Primer Sealer**

<b>Description:</b>	An all purpose interior alkyd primer sealer designed for surfaces with uneven porosity due to repairs, wear or abuse. Its characteristics include quick dry, excellent adhesion and outstanding hold out properties. 567 Assures uniform results with any topcoat, oil or latex. Highly recommended for surfaces that may be contaminated with traces of body oils, waxes or cooking greases.
<b>Recommended Uses:</b>	Especially recommended for use on new plaster, wood masonry and drywall construction. May also be used under wall covering, however, a minimum of 48 hours dry time is required.
<b>Surface Preparation:</b>	Surfaces to be painted must be dry and free from dirt, dust, oil calcimine, loose paint and grease. Surfaces such as kitchen cabinets, frames and moldings around doors and windows that may be contaminated with body oils and cooking grease should be washed with strong detergent, then thoroughly rinsed and allowed to dry before painting.
<b>Application:</b>	<p>For best results, use:</p> <p><b>Brush:</b> A good quality bristle brush</p> <p><b>Roller:</b> ¼" nap roller cover for smooth surfaces and 3/8" to 1/2" nap roller for rough and textured surfaces</p> <p><b>Spray:</b> For airless a tip size from 0.018" to 0.021" is suggested with equipment that will maintain a sufficient fluid pressure to obtain an 8" to 10" fan at one foot distance. For conventional spray, use 0.028" to 0.07" fluid nozzle with air pressure to give 6" to 12" spray pattern at 8" to 12" distance.</p>
<b>Finish:</b>	60° Gloss – 5 to 10 Flat with Low Lustre
<b>Colors:</b>	White Only
<b>Viscosity:</b>	85 – 90 KU
<b>Weight Per Gallon:</b>	10.9 – 11.2 pound per gallon

Revised 2/2/2004

<b>Coverage:</b>	One coat will seal most surfaces and provide an excellent hold out for subsequent topcoating										
<b>Spreading Rate:</b>	Covers 400 – 450 sq. ft. per gallon. Less on porous surfaces.										
<b>Dry Time:</b>	4 to 8 hours under normal conditions. May take longer to dry when humidity is high										
<b>Thinning:</b>	Generally not required. If thinning is desired, up to ½ pint of mineral spirits per gallon of primer										
<b>Clean Up:</b>	Hands and towels can be cleaned with mineral spirits										
<b>Flash Point:</b>	101°F (Closed Cup)										
<b>Formulation:</b>	<b>Pigment 50.0%</b> Titanium Dioxide, Type II.....22.4% Calcium Carbonate.....77.3% Silicates..... <u>0.3%</u> 100.0%  <b>Vehicle 50.0%</b> Alkyd Resin.....30.7% Mineral Spirits.....68.3% Additives & Driers..... <u>1.0%</u> 100.0%										
<b>Packaging:</b>	<table> <tr> <th></th><th><b>Per Case</b></th><th><b>Approx. Weight</b></th></tr> <tr> <td>Gallons</td><td>4</td><td>45 Pounds</td></tr> <tr> <td>Quarts</td><td>6</td><td>17 Pounds</td></tr> </table>		<b>Per Case</b>	<b>Approx. Weight</b>	Gallons	4	45 Pounds	Quarts	6	17 Pounds	
	<b>Per Case</b>	<b>Approx. Weight</b>									
Gallons	4	45 Pounds									
Quarts	6	17 Pounds									
<b>Caution:</b>	Keep out of reach of children. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Use adequate ventilation. Do not apply when temperature is below 40°F to avoid spontaneous combustion, be sure to properly dispose of rags by putting them in closed containers.										

## **DISCLAIMER:**

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

**NOTICE:** Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.