

Muralo 683 Spackle[®] Lite Wall Repair Compound

Description:	A new ready to use wall repair compound based on hollow glass micro-spheres that will not shrink, sag or crack. Fills even large holes and deep cracks in one application. Unlike other lightweight patching compounds, Spackle Lite goes on easy, stays in place, sands easily and can be applied to a feather edge. It may be painted over with latex or oil-based paint when dry.
Recommended Uses:	For interior use in filling holes, cracks and gouges on wallboard, plaster, wood, stucco and masonry.
Surface Preparation:	Surfaces must be clean, dry and free from dirt, dust, loose plaster, grease, wax, or foreign matter. Roughen smooth surfaces with sand paper.
Application:	Stir compound if necessary and apply with a broad putty knife. Spread compound evenly, pressing into holes and cracks, and feathering out the edges. Apply slight excess, overlapping edges of deep cracks and holes. Sand even with surface, using fine sand paper, only after compound has been allowed to dry thoroughly. Primer is recommended for all paints except for Latex Flat. Use recommended primer for the desired finish.
Clean Up:	Soap and water
Weight/Gal:	3.9 + 0.2
Color:	White
Viscosity:	Smooth Paste
Dry Time:	Varies with substrate porosity, film thickness, temperature and humidity. Under normal conditions (70°F, 50% RH) thin applications will dry in less than 1 hour while thicker films may take longer to dry.
Flash Point:	None (closed cup)
Cautions:	Protect against freezing. Do not apply below 45°F. Do not take internally. Close container after each use. Keep out of reach of children.

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.

Revised 2/2/2004