

Exterior Spackle[®] 682

Description	Exterior Spackle [®] is the famous Spackle [®] surfacing compound especially adapted for exterior use. It is ready-mixed for immediate use.
Recommended Uses:	Fill and seal nail heads, cracks, alligatored paint. Smooth unsightly scars left by blistering, peeling paint.
Surface Preparation:	Prime with Exterior Primer.
Application:	Surface must be free of dust, dirt, loose peeling paint, chalk. Sand glossy spots to assure adhesion and then prime. Spread Spackle [®] with a broad knife. Apply sparingly to avoid sanding. It is easier to apply two light coats than one heavy coat that must be sanded. Wash tools in water.
Priming:	Priming with a good exterior primer is necessary.
Colors:	White
Weight Per Gallon:	13.05 ± .15#
Viscosity:	Smooth paste
Dry Time:	Depends on thickness of application. Can be primed when set to touch.
Freeze Thaw:	Keep from freezing.
V.O.C. (VOS):	Contains max. 250 gms. VOC per liter or 2.1 lbs. VOC per gallon.
Caution:	Do not take internally, Keep out of reach of children. Do not apply when temperature is below 45°F. Close container after each use.
Architects Specifications:	Surfaces noted in the accompanying schedule, after receiving proper surface treatment described, shall be finished with Muralo Exterior Spackle [®] . It shall be delivered in the original unopened cans and applied in accordance with directions furnished by the Muralo Company, Inc., manufacturers of Muralo Exterior Spackle [®] , and whose directions are made a part of these specifications.

DISCLAIMER

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead.

Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.

Revised 3/10/2004

Solids by Weight: 73.6%

Packaging:	Per Case	Weight
½ Pint	12	12 lbs.
Quarts	6	22 lbs.
Gallons	4	59 lbs.

Cautions: Keep out of reach of children. Keep from freezing. Do not apply in temperatures below 45°F. Do not take internally. Close container after each use.

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.

Spackle® is a registered trademark of the Muralo Company